



DUNE Supreme

The ever popular DUNE Supreme, with its microperforated, finely sanded surface, combines good levels of sound absorption and sound attenuation, making it the first choice for many spaces.

Key features

- Enhanced acoustical intelligibility
- Wide variety of size and edge details
- Improved durability
- Microperforated

Application areas

Ideal for school environments, classrooms, offices...



Inspiring Great Spaces®

Armstrong®
CEILING SOLUTIONS

DUNE Supreme

EDGE DETAIL	BOARD		TEGULAR		MICROLOOK																														
THICKNESS (mm)	15		15		15																														
MODULES (mm)	600 x 600 2271M 1200 x 600 2272M		600 x 600 2273M		600 x 600 2274M																														
SUSPENSION SYSTEMS	Prelude 24 XL ² / TL ² Prelude 24 Sixty ² XL ² / TL ²		Prelude 24 XL ² / TL ² Prelude 24 Sixty ² XL ² / TL ²		Prelude 15 TL / XL ² Interlude HRC XL ²																														
COLOURS	<div><div>Global White</div><div>Carrara (CA)</div><div>Platinum (PN)</div><div>Blue Mountain (BT)</div></div> <div>COLORTONE DUNE eVo¹</div> <div>¹ See the Colortone DUNE eVo page for available modules.</div>																																		
SUSTAINABILITY	<div><div> 44</div><div></div><div> A</div><div> E1</div></div>																																		
ACOUSTICS	<div><div> EN ISO 10848-2 & EN ISO 717-1</div><div> EN ISO 140-3 & EN ISO 717-1</div><div> EN ISO 354 & EN ISO 11654</div></div> <table><thead><tr><th></th><th>D_{nfw}</th><th>R_w</th><th>α_w</th><th>Class</th><th>NRC</th><th>125</th><th>250</th><th>500</th><th>1000</th><th>2000</th><th>4000</th></tr></thead><tbody><tr><td>Board, Tegular, MicroLook</td><td>35 dB</td><td>17 dB</td><td>0.55</td><td>D</td><td>0.50</td><td>0.40</td><td>0.45</td><td>0.55</td><td>0.60</td><td>0.50</td><td>0.45</td></tr></tbody></table>												D _{nfw}	R _w	α _w	Class	NRC	125	250	500	1000	2000	4000	Board, Tegular, MicroLook	35 dB	17 dB	0.55	D	0.50	0.40	0.45	0.55	0.60	0.50	0.45
	D _{nfw}	R _w	α _w	Class	NRC	125	250	500	1000	2000	4000																								
Board, Tegular, MicroLook	35 dB	17 dB	0.55	D	0.50	0.40	0.45	0.55	0.60	0.50	0.45																								
FIRE REACTION	<div><div></div><div>EEA Euroclass A2-s1, d0 EN 13501-1</div><div>RUS KM1 (G1, V1, D1, T1) FZ 123</div></div>																																		
OTHER PERFORMANCES & FEATURES	<div><div> 84%</div><div> λ = 0.060 W/m K EN 12667 & ISO 8301</div><div> 99% RH</div><div> 3.6 kg/m²</div><div></div><div></div><div></div><div><div>30YEAR system guarantee</div><div>BIM READY</div></div></div>																																		
CUSTOM OPTIONS	<div><div></div><div>Dimensions</div></div>																																		