

STIX A200 MULTI VINYL

MULTI-PURPOSE ADHESIVE FOR ALL VINYL AND TEXTILE COVERINGS

KEY BENEFITS

- **Rapid curing**
- **High initial grab**
- **PVC bonding on old PVC**
- **Long working time**
- **Resistant to castor wheels**
- **Suitable on heated floors**



APPLICATIONS

DESCRIPTION

STIX A 200 MULTI FLOOR has a high initial tack with a long open time. It's an universal multi-uses adhesive able to install most of the soft floorings. For floor and wall

DESTINATION

For all types of resilient flooring in private/public or collective buildings.
It's a universal multi-purpose adhesive suitable for the installation of most soft floor coverings.
Recommended by most of the manufacturers
For interior use only.

Associated floor coverings :

- Homogeneous and heterogeneous PVC sheeting and tiles
- Cork with PVC backing
- Expanded vinyl
- Semi-flexible tiles
- Textiles: needle punch with or without backing, foam
- Non-woven textile floor coverings
- Natural fiber floor coverings (Coir, sisal and sea grass).

PRODUCT CHARACTERISTICS

Composition/ colour	Acrylic water based/ cream
Waiting time*	10-15min
Open time*	45-50min
Walk on time*	12 hours
Curing time*	24 to 48 hours
Coverage	250-400 g/m ²
Application temperature	10 to 25°C
Frost sensitivity	Reversible up to 0°C

*these times are determined at + 23° C and 50 % relative humidity on normally absorbent substrates

SUBFLOOR PREPARATION

CLEANING PREPARATION

Preparation should be in accordance with building standards. Subfloors must be sound, smooth, permanently dry and free from old adhesive residues, dust, grease or other contaminants.

When overlaying existing floor coverings ensure that they are firmly bonded and clean.

Remove dirt, polish, oil and similar contaminating substances.

Need to comply with local regulation and mostly prepared with a self-leveling compound associated with Bostik primers.

Very absorbent surfaces must be primed to prevent over absorption. Anhydrite screeds as well as particleboards and plywood should be primed with dedicated primer.

Always allow primers and self-levelling underlayment to dry thoroughly before applying the adhesive.

METHOD OF USE

Apply an even coat over the whole area to be covered using a suitable notched trowel (depending on the porosity and roughness of the substrate).

Type of floor covering or specific substrate

Notched trowel to be used (TKB standard)

Average consumption, per m²

- Very thin floor coverings with a smooth backing on all types of substrates or floor coverings with a smooth backing on non-porous substrates (A4 type or by roller/ 200 g/m²)
- Floor coverings with a smooth backing (A2 type / 200-250 g /m²)
- Floor coverings with a slightly rough backing (B1 type / 300-350 g/m²)

Bonding PVC onto PVC, impervious surfaces: open time can vary from 30 to 90 minutes depending on

ambient conditions and the quantity of adhesive applied.

COVERAGE

From 250 to 400 g/m² depending on the type of coating and the spatula used.

STORAGE STABILITY

Up to 12 months in the original unopened container stored between +10°C and +30°C. Frost-sensitive

CLEANING

Tools should be cleaned with warm water, preferably whilst the adhesive is still wet.

Code	UC	PCB	GENCOD
30615675	6 kg	1	3549212484828
30615552	20 kg	1	3549212484804

SAFETY

For more details, consult the safety data sheet on

<https://bostiksdcs.thewerco.com/default.aspx>

The information given and recommendations made herein are based on Bostik's research only and are not guaranteed to be accurate. The performance of the product, its shelf life, and application characteristics will depend on many variables, including the kind of materials to which the product will be applied, the environment in which the product is stored or applied, and the equipment used for application. Any change in any of these variables can affect the product's performance. It is the buyer's obligation, prior to using the product, to test the suitability of the product for an intended use under the conditions that will exist at the time of the intended use. Bostik does not warrant the product's suitability for any particular application. The product is sold pursuant to Bostik's Terms and Conditions of Sale that accompanies the product at the time of sale. Nothing contained herein shall be construed to imply the nonexistence of any relevant patents or to constitute permission, inducement, or recommendation to practice any invention covered by any patent, without authority from the owner of the patent.

BOSTIK TECHNICAL ASSISTANCE

Please contact your local representative

